according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 570

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm

responsible for the SDS

mcm@oks-germany.com

Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num: +49 8142 3051 517

ber Warszawa: +48 22 619 66 54

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters air-

ways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use alcohol-resistant foam,

carbon dioxide or water mist to extinguish.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

butanone

acetone

xylene



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solvent

Silicone resin

PTFE

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35- XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 30 - < 50
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43- XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 10 - < 20
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49- XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-21119475103-46- XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066	>= 1 - < 10
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32- XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 STOT RE2; H373 Asp. Tox.1; H304	>= 1 - < 10
methanol	67-56-1 200-659-6 603-001-00-X 01-2119433307-44- XXXX	Flam. Liq.2; H225 Acute Tox.3; H301 Acute Tox.3; H331 Acute Tox.3; H311 STOT SE1; H370	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression

Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Unsuitable extinguishing

media

: High volume water jet



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not let product enter drains.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod: :

ucts

Carbon oxides

Halogenated compounds

Metal oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13). Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only in an area containing explosion proof equipment.

Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

Do not enter areas where used or stored until adequately ven-

tilated.

Do not repack.

Do not re-use empty containers.

These safety instructions also apply to empty packaging which

may still contain product residues. Keep container closed when not in use.

Advice on protection against :

fire and explosion

Keep away from heat and sources of ignition.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regu-

lations. Keep in properly labelled containers.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

	104011	T. (/=		I 5 ·
Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butanone	78-93-3	TWA	200 ppm	2000/39/EC
			600 mg/m3	(2000-06-16)
	Further infor	mation: Indicative		
		STEL	300 ppm	2000/39/EC
			900 mg/m3	(2000-06-16)
	Further infor	mation: Indicative		,
		NDS	450 mg/m3	PL OEL
			133g,3	(2018-07-07)
	Further infor	mation: Skin	l	(======================================
		NDSch	900 mg/m3	PL OEL
				(2018-07-07)
	Further infor	mation: Skin		(======================================
acetone	67-64-1	TWA	500 ppm	2000/39/EC
			1.210 mg/m3	(2000-06-16)
	Further infor	mation: Indicative		, , , , , , , , , , , , , , , , , , , ,
		NDS	600 mg/m3	PL OEL
			333g,	(2018-07-07)
		NDSch	1.800 mg/m3	PL OEL
		1120011	11000 111g/1110	(2018-07-07)
ethyl acetate	141-78-6	NDS	734 mg/m3	PL OEL
Cirryr doctate	141700	NDO	704 mg/mo	(2018-07-07)
		NDSch	1.468 mg/m3	PL OEL
		1120011	1. 100 mg/me	(2018-07-07)
		STEL	400 ppm	2017/164/EU
		OTEL	1.468 mg/m3	(2017-02-01)
	Further infor	mation: Indicative	1.100 mg/me	(2017-02-01)
	T draior iiiioi	TWA	200 ppm	2017/164/EU
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	734 mg/m3	(2017-02-01)
	Further infor	mation: Indicative	104 mg/mo	(2017-02-01)
xylene	1330-20-7	TWA	50 ppm	2000/39/EC
Aylono	1000 20 7	1 7 7 7	221 mg/m3	(2000-06-16)
	Further infor	mation: Identifies the	possibility of significant up	
	skin, Indicati		possibility of significant up	stake tillough the
	JKIII, IIIGIGALI	STEL	100 ppm	2000/39/EC
			442 mg/m3	(2000-06-16)
	Further infor	mation: Identifies the	possibility of significant up	
	skin, Indicati		possibility of significant up	Jiake illibugii ille
	,	NDS	100 mg/m3	PL OEL
				(2018-07-07)
	Further infor	mation: Skin	•	, ,
		NDSch	200 mg/m3	PL OEL
				(2018-07-07)
	Further infor	mation: Skin	1	//

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

VersionRevision Date:Date of last issue: 11.07.2022Print Date:1.516.01.2023Date of first issue: 09.07.201616.01.2023

methanol	67-56-1	TWA	200 ppm	2006/15/EC	
			260 mg/m3	(2006-02-09)	
	Further inform	nation: Indicative, Ide	entifies the possibility of signif	ficant uptake	
	through the s	kin			
		NDS	100 mg/m3	PL OEL	
				(2018-07-07)	
	Further inform	Further information: Skin			
		NDSch	300 mg/m3	PL OEL	
			_	(2018-07-07)	
	Further inform	nation: Skin			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	, ,	5 5	` '	
Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Skin contact	Long-term systemic effects	63 mg/kg
xylene	Workers	Inhalation	Long-term exposure, Systemic effects	77 mg/m3
	Workers	Inhalation	Short-term exposure, Systemic effects	289 mg/m3
	Workers	Skin contact	Long-term exposure, Systemic effects	180 mg/kg
	Consumers	Inhalation	Long-term exposure, Systemic effects	14,8 mg/m3
	Consumers	Inhalation	Short-term exposure, Systemic effects	174 mg/m3
	Consumers	Ingestion	Long-term exposure, Systemic effects	1,6 mg/kg
methanol	Workers	Inhalation	Long-term systemic effects	130 mg/m3
	Workers	Inhalation	Acute systemic effects	130 mg/m3
	Workers	Inhalation	Long-term local ef- fects	130 mg/m3
	Workers	Inhalation	Acute local effects	130 mg/m3
	Workers	Skin contact	Long-term systemic	20 mg/kg

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

			effects	bw/day
	Workers	Skin contact	Acute systemic ef-	20 mg/kg
			fects	bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg
ethyl acetate	Fresh water	0,24 mg/l
	Marine water	0,024 mg/l
	Sewage treatment plant	650 mg/l
	Fresh water sediment	1,15 mg/kg
	Marine sediment	0,115 mg/kg
	Soil	0,148 mg/kg
xylene	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/l
	Marine sediment	12,46 mg/l
	Soil	2,31 mg/kg
methanol	Fresh water	20,8 mg/l
	Marine water	2,08 mg/l
	Intermittent use/release	1540 mg/l
	Microbiological Activity in Sewage Treat- ment Systems	100 mg/l
	Fresh water sediment	77 mg/kg
	Marine sediment	7,7 mg/kg
	Soil	3,18 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Remarks : Protective gloves The choice of an appropriate glove does

not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore

has to be measured for each case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : white

Odour : solvent-like

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : 71,5 °C (1.013 hPa)

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

11,5 %(V)

Lower explosion limit / Lower

flammability limit

1,0 %(V)

Flash point : -19,00 °C

Method: DIN 51755, closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-polar/aprotic

Viscosity

Viscosity, dynamic : No data available



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

Viscosity, kinematic : < 6,9 mm2/s (40 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 168 hPa (20 °C)

Relative density : 0,83 (20 °C)

Reference substance: Water The value is calculated

Density : 0,83 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

 Version
 Revision Date:
 Date of last issue: 11.07.2022
 Print Date: 16.01.2023

 1.5
 16.01.2023
 Date of first issue: 09.07.2016
 16.01.2023

Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central

nervous system depression

Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

 Version
 Revision Date:
 Date of last issue: 11.07.2022
 Print Date: 16.01.2023

 1.5
 16.01.2023
 Date of first issue: 09.07.2016
 16.01.2023

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg

Assessment: The substance or mixture has no acute dermal

toxicity

butanone:

Acute oral toxicity : LD50 (Rat): 2.193 mg/kg

Method: OECD Test Guideline 423

GLP: yes

Acute inhalation toxicity : LC50 (Rat): 34 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

ethyl acetate:

Acute oral toxicity : LD50 (Rat): 5.620 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

xylene:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after

single contact with skin.

methanol:

Acute oral toxicity : LD50 (Rat): 5.600 mg/kg

Assessment: The component/mixture is toxic after single in-

gestion.

Acute inhalation toxicity : LC50 (Rat): 64000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50 (Rabbit): 15.800 mg/kg

Assessment: The component/mixture is toxic after single con-

tact with skin.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

butanone:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

acetone:

Result : Repeated exposure may cause skin dryness or cracking.

ethyl acetate:

Species : Rabbit

Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

xylene:

Species : Rabbit

Assessment : Irritating to skin. Result : Irritating to skin.

methanol:

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

butanone:

Species : Rabbit

Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Result : Irritating to eyes.

acetone:

Species : Rabbit Result : Eye irritation

ethyl acetate:

Assessment : Irritating to eyes. Result : Irritating to eyes.

xylene:

Species : Rabbit

Assessment : Irritating to eyes. Result : Irritating to eyes.

methanol:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

butanone:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

ethyl acetate:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

xylene:

Species : Mouse

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 429

Result : Did not cause sensitisation on laboratory animals.

methanol:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Rodent cell line Method: OECD Test Guideline 473

Result: negative

butanone:

Germ cell mutagenicity- As-

sessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

xylene:

Germ cell mutagenicity- As-

sessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

butanone:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

xylene:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

Remarks: No data available

Components:

butanone:

Reproductive toxicity - As-

sessment

- Fertility -

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

xylene:

Reproductive toxicity - As-

sessment

Fertility -

No toxicity to reproduction

- Teratogenicity -

No toxicity to reproduction

STOT - single exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

butanone:

Exposure routes : Inhalation

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.,

May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

ethyl acetate:

Exposure routes : Inhalation

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

xylene:

Exposure routes : Inhalation

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with respiratory tract

irritation.

methanol:

Exposure routes : Ingestion

Target Organs : Central nervous system, Eyes

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 1.

Exposure routes : Inhalation

Target Organs : Central nervous system, Eyes

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 1.

Exposure routes : Skin contact

Target Organs : Central nervous system, Eyes

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 1.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)

Assessment : No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

butanone:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

ethyl acetate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

xylene:

Exposure routes : Inhalation

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Exposure routes : Ingestion
Target Organs : Liver, Kidney

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

butanone:

No aspiration toxicity classification

xylene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.

Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.
Possible risk of irreversible effects.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

: EbC50 (Pseudokirchneriella subcapitata (green algae)): 26

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

 Version
 Revision Date:
 Date of last issue: 11.07.2022
 Print Date: 16.01.2023

 1.5
 16.01.2023
 Date of first issue: 09.07.2016
 16.01.2023

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 308 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 1.972

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): 1.150 mg/l

Exposure time: 16 h Test Type: static test Method: DIN 38 412 Part 8

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 212,5 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 154 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2.500

mg/l

Exposure time: 96 h

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 3,82 mg/l

Exposure time: 48 h

Test Type: flow-through test

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2

mg/l

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

 Version
 Revision Date:
 Date of last issue: 11.07.2022
 Print Date: 16.01.2023

 1.5
 16.01.2023
 Date of first issue: 09.07.2016
 16.01.2023

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 157 mg/l

Exposure time: 3 h

Test Type: Respiration inhibition Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox-

icity)

NOEC: > 1,3 mg/l Exposure time: 56 d

Species: Oncorhynchus mykiss (rainbow trout)

Test Type: flow-through test

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC50: 2,90 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: static test

Method: OECD Test Guideline 211

GLP: yes

methanol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 290 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 22.000

mg/l

Exposure time: 96 h Test Type: static test

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l

Exposure time: 3 h

Test Type: Growth inhibition

Method: OECD Test Guideline 209

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removabil- :

ity

Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

Biodegradability Result: Readily biodegradable.

butanone:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: rapidly biodegradable

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 301D

GLP: yes

acetone:

Biodegradability Result: rapidly biodegradable

ethyl acetate:

Biodegradability Result: rapidly biodegradable

xylene:

Biodegradability Result: Readily biodegradable.

methanol:

Biodegradability Result: Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Remarks: This mixture contains no substance considered to Bioaccumulation

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

butanone:

Remarks: Due to the distribution coefficient n-octanol/water, Bioaccumulation

accumulation in organisms is not expected.

Partition coefficient: n-

log Pow: 0,3 (40 °C)

octanol/water

Method: OECD Test Guideline 117

GLP: yes

acetone:

Remarks: Does not bioaccumulate. Bioaccumulation

Partition coefficient: n-

octanol/water

log Pow: 0,2



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

 Version
 Revision Date:
 Date of last issue: 11.07.2022
 Print Date: 16.01.2023

 1.5
 16.01.2023
 Date of first issue: 09.07.2016
 16.01.2023

ethyl acetate:

Partition coefficient: n-

octanol/water

: log Pow: 0,68 (25 °C)

xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9

Partition coefficient: n-

octanol/water

log Pow: 2,77 - 3,15

methanol:

Bioaccumulation : Bioconcentration factor (BCF): 0,2

Partition coefficient: n-

octanol/water

log Pow: -0,77

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Components:

butanone:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

xylene:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

methanol:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of waste product or used containers according to

local regulations.

The following Waste Codes are only suggestions:

Waste Code : used product, unused product

08 01 11*, waste paint and varnish containing organic sol-

vents or other hazardous substances

uncleaned packagings

15 01 10*, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT

(naphtha (petroleum), hydrotreated light)

IATA : Paint

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 364

aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 16.01.2023 Date of first issue: 09.07.2016 16.01.2023 1.5

Packing instruction (passen-353

ger aircraft)

Packing instruction (LQ) Y341 Packing group Ш

Labels Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous yes

Environmentally hazardous yes

Environmentally hazardous yes

IMDG

Marine pollutant yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances.

mixtures and articles (Annex XVII)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

(EU SVHC)

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer (EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast) (EU POP)

Not applicable

Article 57).

Not applicable

Not applicable

Regulation (EC) No 649/2012 of the European Parlia-Not applicable

> a brand of FREUDENBERG

Conditions of restriction for the fol-

This product does not contain sub-

stances of very high concern (Regu-

lation (EC) No 1907/2006 (REACH),

Number on list 3

lowing entries should be considered:

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

ment and the Council concerning the export and import of dangerous chemicals

(EU PIC)

Regulation (EU) 2019/1148 on the marketing and use of : Listed

explosives precursors

This product is regulated by Regulation (EU) 2019/1148: acetone (ANNEX II)

all suspicious transactions, and significant disappearances and thefts should be reported to the relevant na-

tional contact point. Please see

https://ec.europa.eu/home-affairs/sites/ homeaf-

fairs/files/what-we-do/policies/crisis-and-

terrorism/explosives/explosives-

precur-

sors/docs/list_of_competent_authorities_and_national_c

ontact points en.pdf

: P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous sub-

stances.

E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 82,06 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Act of 25 February 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2019, No. 0, item 1225)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC,

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878

Ordinance of the Minister of Health of 10 August 2012 concerning the criteria and procedure of classification of chemical substances and their mixtures (consolidated text Dz. U. of 2015., pos. 208).

Ordinance of the Minister of Economy, Labour and Social Policy of 21st December 2005 concerning the basic requirements for personal protective equipment (Dz. U. Nr. 259, item 2173). Ordinance of the Minister of Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 wraz z późn. zm.). Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended). Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended). Act of 13 June 2013. On packaging and packaging waste Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 18 February 2019 on enforcing of changes Annexes A and B of Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. 2019, item 769).

Ordinance of the Minister of Health of 20th April 2012 concerning labeling of containers of dangerous substances and dangerous mixtures and some mixtures ((consolidated text) Dz. U. z 2015 nr. 0 poz. 450).

Ordinance of the Minister of Health of 11th June 2012 concerning categories of dangerous substances and dangerous mixtures for which containers must be fitted with child-resistant fastenings and a tactile warning of danger (Dz. U. from 2012, item 688 as amended).

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

H225 : Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H301 : Toxic if swallowed.

H304 : May be fatal if swallowed and enters airways.

H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570		
Version 1.5	Revision Date: 16.01.2023	Date of last issue: 11.07.2022 Print Date: Date of first issue: 09.07.2016 16.01.2023
H331 H332 H335 H336 H370 H373		 Toxic if inhaled. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to organs. May cause damage to organs through prolonged or repeated
H373 H411 EUH0	66	 exposure if inhaled. : May cause damage to organs through prolonged or repeated exposure if swallowed. : Toxic to aquatic life with long lasting effects. : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

classes, e.g. STOT, the route of exposure should be indicating in the hazard statement only if it is conclusively proven that other route of exposure can cause the hazard in accordance to the criteria in Annex I. Under Directive 67/548/EEC the route of exposure was indicated for classifications with R48 when there was data justifying the classification for this rout of exposure. The classification under 67/548/EEC indicating the route of exposure has been translated into the corresponding class and category according to this Regulation, but a general hazard statement not specifying the route of	t no ce 3 ite g but
exposure as the necessary information is not available. Note C : Some organic substances may be marketed either in a spe ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.	
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a fi list of indicative occupational exposure limit values	irst
2006/15/EC : Europe. Indicative occupational exposure limit values	
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values	l
PL OEL : Poland. Occupational exposure limits for airborne toxic sub stances)-
2000/39/EC / TWA : Limit Value - eight hours	
2000/39/EC / STEL : Short term exposure limit	
2006/15/EC / TWA : Limit Value - eight hours	
2017/164/EU / STEL : Short term exposure limit	
2017/164/EU / TWA : Limit Value - eight hours	
PL OEL / NDS : Maximal Admissible Concentration	
PL OEL / NDSch : Maximal Admissible Temporary Concentration	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Test-



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

 Version
 Revision Date:
 Date of last issue: 11.07.2022
 Print Date:

 1.5
 16.01.2023
 Date of first issue: 09.07.2016
 16.01.2023

ing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Chronic 2	H411	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 570

Version Revision Date: Date of last issue: 11.07.2022 Print Date: 1.5 16.01.2023 Date of first issue: 09.07.2016 16.01.2023

the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.