



Numer produktu: 0207047

### Suction cup F-OB 30x60 Silicone, G1/8"male SS, FCM

- The silicone material complies with FDA 21 CFR 177.2600 and EU 1935/2004.
- Transparent color without pigment
- Long lasting high-end silicone material
- Excellent grip on oblong parts such as flow-packs and stick-packs
- Available with threaded and integrated stainless steel fittings.
- Easy to clean with hygienic design. No dust/dirt pockets.

#### Ogólne

Aplikacja	Zgodność ze standardem FDA UE
Kształt	Owalne mieszki
Materiał	SILNONDETFCM, ASTM316L
Model przyssawki	F-OB
Waga	53,14 g
Objętość	17,5 cm <sup>3</sup>
Suction cup model	F-OB 30x60
Movement, vertical max.	10,9 mm
Minimalny promień krzywizny	11 mm

#### Mocowanie



Opcje mocowania	Brak
Wymiar mocowania	1/8"
Rodzaj mocowania	Męskie
Rodzaj mocowania	Gwint typu G

#### Wymiar

Wysokość	44,8 mm
Długość	62 mm
Szerokość	32 mm

---

#### Wydajność - siła podnoszenia

	F-OB 30x60		
10 -kPa		8 N	8,1 N
20 -kPa		17,2 N	13,4 N
40 -kPa		31,1 N	27,5 N

---

#### Materiał

Nazwa	SILNONDETFCM
Kolor	Transparent
Minimalna temperatura	-40 - 200 °C
Twardość	40 °Shore A

---

	SILNONDETFCM
Alkohol	++
Stężone kwasy	-
Etanol	n/a
Hydroliza	+
Metanol	n/a
Olej	-
Utlenianie	+++
Benzyna	-
Odporność na zużycie	++
Warunki atmosferyczne i ozon	+++

---

Rysunki wymiarowe 

Ta czynność wymaga zalogowania się  
Proszę [Login](#) lub [Zarejestruj](#), aby otrzymać pełne korzyści z piab.com.

---