

RoHS

For general pneumatic tubing Flexible Polyurethane tubing





Burst Pressure Characteristics Curve and Operating pressure



Model

■ – 20 m roll Tubing size Inch size Metric size (Series TIUR) (Series TU) Model 10-TIUB01 | 10-TU0212 | 10-TU0425 | 10-TU0604 | 10-TU0805 | 10-TU1065 | 10-TU1208 O.D. (mm) 3.2 1.2 2.5 I.D. (mm) 6.5 Black (B) White (W) Red (R) Blue (BU) Yellow (Y) Green (G) Clear (C) Orange (YR)

∧ Precautions

Be sure to read this before handling. Refer to page 1382 for Safety In-I I structions and pages 1237 to 1240 I for Fittings and Tubing Precautions.

⚠ Caution

- Applicable for general industrial water.

 Please consult with SMC if using for the other kind of fluid. Also, the surge voltage pressure must be under the maximum operating pressure. If the surge pressure exceeds the maximum operating pressure, it will result in damage to fittings and tubes.
- 2. The value of the max. operating pressure is at a temperature of 20°C. Refer to the burst pressure characteristics curve for other temperatures. Furthermore, abnormal temperature rises caused by adiabatic compression may result in the burst of the tube.
- 3. The value of the minimum bending radius is measured at the temperature of 20°C as shown in the figure on the right.

Specifications						
Fluid	Air, Water					
Max. operating pressure (20°C)	0.8 MPa					
Burst pressure	Refer to the burst pressure characteristics curve.					
Recommended fittings	Clean series fittings 10-KQ2, 10-KF, 10-KDM, 10-KG 10-M, 10-MS, KP, KPQ, KPG					
Min. bending radius (mm)	10	4	15	20	27	35
Operating temperature	-20 to 60°C, Water: 0 to 40°C (No freezing)					
Material	Polyurethane					
Cleanliness class (ISO class)	Class 3					



Bend the tube into U-form at a temperature of 20°C. Fix one end and close loop gradually. Measure 2R when the tube breaks or is crushed.

Air