



Donaldson  
FILTRATION SOLUTIONS

## DATA SHEET

### Filter media

Polyester Anti-Static + PTFE Membrane (Food)

### Polyester Anti-Static + PTFE Membrane (Food)

<b>Treatment</b>	Anti-Static + PTFE Membrane
<b>Use</b>	Pleatable filter media
<b>Composition</b>	100% Polyester
<b>Area weight</b>	260 g/m <sup>2</sup>
<b>Thickness</b>	0.48 mm
<b>Air Permeability</b>	200 m <sup>3</sup> /m <sup>2</sup> /h at 200 Pa
<b>Surface electrical resistance</b> (Ohm) Measured according DIN EN 1149-1	5 x 10 <sup>3</sup> on the metallic coated side of the media
<b>IFA/BIA certificate</b> (DIN EN 60335-2-69:2015)	M
<b>Temperature (dry heat)</b>	
Continuous	120 °C
Peaks	140 °C
<b>Chemical resistance</b>	
Oil/Water	Excellent
Hydrolysis	Very Good
Acid	Good
Alkali	Good
<b>Dust release</b>	Excellent
<b>Suitable application</b>	When there is a requirement for conformity to EU regulation No. 10/2011/EC as amended by regulation No. 321/2011/EC, 1183/2011/EC and 2015/174/EC as well as FDA, on materials intended to come into contact with foodstuff.

Order online

shop.Donaldson.com

Contact us

Donaldson.com

Publication DOCAM12160N • Rev. 01 • 0322

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.