



Donaldson
FILTRATION SOLUTIONS

DATA SHEET

Filter media

Torit-TEX™

Torit-TEX™

Product code	9032
Appearance	White, uncorrugated
Use	Pleatable filter media
Composition	Spunbond polyester with ePTFE membrane
Area weight (DIN 53884)	260 g/m ²
Thickness (DIN 53885)	0.6 mm
Air Permeability (DIN 53887)	35–60 l/dm ² /min @ 200Pa
Surface finish	Tetratex® Extreme ePTFE membrane
Surface electrical resistance (DIN 54345)	N/A
ISO Classification ISO 16890-2:2016(E) CERTIFICATE	ePM ₁ 80% Test report number: 163-2
Temperature (dry heat)	
Continuous	120 °C
Chemical resistance	
Hydrolysis	N/A
Acids	Good
Alkalis	Good
Oxidising agents	Good
Organic solvents	Good
Abrasion resistance	Excellent
Supports combustion	Yes
Application field	Wide pleat spacing and smooth, hydrophobic PTFE membrane provides excellent particle release. Highly recommended for chemical, food and industrial processing, when product contamination must be minimised. Excellent performance on moist, hygroscopic or agglomerative dust.

Order online

shop.Donaldson.com

Contact us

Donaldson.com

Publication 4218048GB • Rev. 12 • 0820

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.