



Donaldson  
FILTRATION SOLUTIONS

## DATA SHEET

### Filter media

Blended 80/20

### Blended 80/20

<b>Appearance</b>	White, corrugated
<b>Use</b>	Pleatable filter media
<b>Composition</b>	Blended Cellulose + Synthetic
<b>Area weight</b>	130 g/m <sup>2</sup>
<b>Thickness</b>	0.35 mm
<b>Air Permeability (Frazier)</b>	540 m <sup>3</sup> /m <sup>2</sup> .h at 125 Pa
<b>IFA/BIA certificate</b> (DIN 660335-2-69)	Class M Test report number: 201723219/6120
<b>Temperature (dry heat)</b>	
Continuous	65 °C
Peaks	80 °C
<b>Chemical resistance</b>	
Hydrolysis	N/A
Acids	Poor
Alkalis	Fair
Oxidising agents	Poor
Organic solvents	Fair
<b>Abrasion resistance</b>	Good
<b>Supports combustion</b>	Yes
<b>Application field</b>	Fine dust fumes caused by laser and plasma cuttind, welding fumes, shot blasting.

Order online

shop.Donaldson.com

Contact us

Donaldson.com

Publication DOCAM0506301 • Rev. 11 • 1118

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.