



Donaldson  
FILTRATION SOLUTIONS

## DATA SHEET

### Filter media

Fibra-Web™

### Fibra-Web™

<b>Appearance</b>	Blue tinted, corrugated
<b>Use</b>	Pleatable filter media
<b>Composition</b>	Synthetic/glass substrate with nanofiber layer
<b>Area weight</b>	114 g/m <sup>2</sup>
<b>Thickness</b>	0.56 mm
<b>Air Permeability (Frazier)</b>	970 m <sup>3</sup> /m <sup>2</sup> .h at 125 Pa
<b>ISO Classification</b> ISO 16890-2:2016(E) CERTIFICATE	ePM <sub>1</sub> 75% Test report number: 164-2
<b>Temperature (dry heat)</b>	
Continuous	65 °C
Peaks	80 °C
<b>Chemical resistance</b>	
Hydrolysis	N/A
Acids	Good
Alkalis	Good
Oxidising agents	Fair
Organic solvents	Good
<b>Abrasion resistance</b>	Excellent
<b>Supports combustion</b>	Yes
<b>Application field</b>	<p>Wide pleat spacing provides thorough pulse cleaning of fibrous and agglomerative particles. Excellent performance on combination fibrous and non-fibrous dust, and/or agglomerative dust. High filtration efficiency on very fine particulate &lt; 1 micron.</p> <p>Composite grinding, food processing, grain handling, metal buffing, pharmaceutical, textiles, woodworking.</p>

Order online

shop.Donaldson.com

Contact us

Donaldson.com

Publication 4218046GB • Rev. 12 • 0820

Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.